

# Technical data sheet

Roof conductor holder for ridge tiles, 180–240 mm, Rd  
8–10, FT  
Item number: 5202566



- Adjustable from 180–240 mm
- With conductor 177/20, polyamide, grey
- With 3 M8 threaded nipples for positioning the holder

<b>St</b>	Steel
<b>FT</b>	Hot-dip galvanised

## Master data

Item number	5202566
Type	132 N-DK
Description 1	Roof conductor holder
Description 2	for ridge tiles
Manufacturer	OBO
Dimension	8mm
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	20
Unit of quantity	Piece
Weight	19.7 kg
Weight unit	kg/100 pc.

## Technical data

Application	Ridge
Conductor fastening type	With clamp clip
Conductor diameter, max.	10
Conductor diameter, min.	8
Mounting type	Tensionable
Mounting height	20 mm

# Technical data sheet

Roof conductor holder for ridge tiles, 180–240 mm, Rd  
8–10, FT  
Item number: 5202566



## Technical data

Fit	Rd 8-10 mm
Clamping range D, max.	240 mm
Clamping range D, min.	180 mm
Material of the holder	Plastic
Material of the support	Steel, hot galvanised