

Technical data sheet

Double push-fit clip

Item number: 2197855



These push-fit clips are used when installing cables and pipes on walls and ceilings and when running flexible pipes on concrete and in the screed. The double push-fit clips can be used instead of nail clips in concrete and aerated concrete. The advantage of the push-fit clips is that they only have to be pushed into the drilled hole. Anchors and bolts are not needed.



PA Polyamide

Master data

| | |
|---------------------|----------------------|
| Item number | 2197855 |
| Type | 1974 2X4-12 |
| Description 1 | Plug-in clip |
| Description 2 | double |
| Manufacturer | OBO |
| Dimension | 4-12mm |
| Colour | Light grey; RAL 7035 |
| Material | Polyamide |
| Smallest sales unit | 100 |
| Unit of quantity | Piece |
| Weight | 0.128 kg |
| Weight unit | kg/100 pc. |

Technical data

| | |
|--------------------------------|----------------|
| Number of cables/pipes | 2 |
| Version for | Two-lobe |
| Fastening type | Plug fastening |
| Drill hole depth | 40 mm |
| Drill hole diameter, min. | 6 mm |
| Breaking load for concrete B25 | 90 N |
| Halogen-free | yes |

Technical data sheet

Double push-fit clip

Item number: 2197855



Technical data

| | |
|------------------------|-------|
| Clamping range D, max. | 12 mm |
| Clamping range D, min. | 4 mm |