

Technical data sheet

Angler spreading anchor

Item number: 2349480



Required minimum screw length = anchor length + component thickness + 1 x screw Ø.
Withdrawal force applies to wood screws of the largest screw diameter, required safety values must be taken into account.




PA Polyamide

Master data

Item number	2349480
Type	910 F 5x25
Description 1	Spreading anchor
Available from	01.05.2020
Manufacturer	OBO
Dimension	5x25
Colour	Light grey
Material	Polyamide
Smallest sales unit	100
Unit of quantity	Piece
Weight	0.042 kg
Weight unit	kg/100 pc.

Dimensions



Length	25 mm
Dimension D	5 mm
Dimension L	25 mm

Technical data sheet

Angler spreading anchor

Item number: 2349480



Technical data

Version for	Universal anchor
Concrete Frat	230
Drill hole depth	30 mm
Drill hole diameter, min.	5 mm
Suitable for fastening with cable ties	no
Suitable for gas concrete	no
Suitable for hexagonal wood screw	yes
Halogen-free	yes
Hollow brick Hlz12 Frat	90
Wood screws	2,5-4
Solid calcareous sandstone KSL12 Frat	330
With edge	no
With bolts	no
Porous concrete P2 Fempf.	40
Porous concrete P4 Fempf.	40
Full brick Mz12 Frat	240