Technical data sheet Cable tray BKRS 100 FS

Item number: 6062002



Heavy-duty, walkable cable tray system BKRS with base perforation, in 100 mm side height.

The cable tray has connector perforations on both sides.

Straight connectors should be ordered separately and in the appropriate quantity. Magnetic shield insulation without cover 20 dB, with cover 50 dB.



ψ _L CE	
St	Steel
FS	Strip galvanized

(


Master data

Item number 6062002 Type BKRS 1020 FS Description 1 Cable tray BKRS Description 2 walkable Manufacturer OBO Discription 2 0200 0000	
Description 1 Cable tray BKRS Description 2 walkable Manufacturer OBO	
Description 2 walkable Manufacturer OBO	
Manufacturer OBO	
Dimension 100x200x3000	
Material Steel	
Surface Strip galvanized	
Surface standard DIN EN 10346	
Smallest sales unit 3	
Unit of quantity Metre	
Weight 614.567 kg	
Weight unit kg/100 m	

Technical data sheet Cable tray BKRS 100 FS

Item number: 6062002





Length	3,000 mm
Length	10 ft
Width	200 mm
Width	8 in
Height	100 mm
Height	4 in
Plate thickness	0.08 in
Plate thickness	2 mm
Dimension B	200 mm
Dimension H	100 mm
Dimension L	3,000 mm

Technical data

Connector version	Without connectors
Mounting system fastening type	Floor
Walkable	yes
Maintain electrical functions	no
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Usable cross-section	171 cm ²
Usable cross-section	17052 mm²
Rustproof steel, pickled	no
Side perforation	no
Wide-span version	no
Load test type according to IEC 61537	Туре II
Type of connector, cable support system	Screwed