# **Technical data sheet**

Junction box, B 9/K M empty, with thread

#### Item number: 2001942





Protection rating IP67, empty box for use with individual terminals, four plastic cover screws, thus absolute corrosion-protection, two fastening bases for screws of up to 5 mm  $\emptyset$ , 7 break-out entries with thread M20 x 1.5. 3 polyamide cable glands for cable diameters of 9–12 mm, type 106 M.

3 cable glands of polyamide for a cable diameter of 9–12 mm, type 106/20 B9K M



Duroplast, Aminoplast

Master data

0001010
2001942
B9KM
Junction box
with 3 cable glands
OBO
94x94x45
Light grey; RAL 7035
Duroplast, Aminoplast
5
Piece
13.5 kg
kg/100 pc.


## **Technical data sheet**

Junction box, B 9/K M empty, with thread

### Item number: 2001942



### Dimensions Length 94 mm Width 94 mm Height 45 mm



#### **Technical data**

٢

Expandable no No. of entries 7 Type of insertion Glar	
Type of insertion Clar	
Type of insertion Giai	nd
Type of entry Cab	le
Type of housing penetration Three	ead and pre-marking
Measured insulation voltage Vi 400	V
Cover Not	transparent
Cover fastening Scre	ewed
Entry from rear no	
Entries 7 bro	eak-out entries with thread M20 x 1.5.
Explosion-tested version no	
Flame-resistant Acc.	to VDE 0471/DIN 695 Part 2-1, test temperature 750°C
Shape Squa	are
Maintain electrical functions With	lout
For Ex zone With	lout
For Ex zone gas With	lout
For Ex zone dust With	lout
for pipe diameter 20 n	าท
Halogen-free yes	
Clear internal dimensions 84x8	34x34 mm
With screening no	
with lid yes	
Nominal cross-section, max. 70 n	nm²
Nominal cross-section, min. 0 mr	m²
Nominal voltage 400	V
Sealable yes	
Impact-resistant no	
Protection rating IP67	,
Weatherproof no	