

# Technical data sheet

## GESR9 service outlet with locking slider

Item number: 7405466



Service outlet with locking slider for up to 12 individual Modul 45 devices in 3 UT4 universal supports, use in duct and trunking systems and system floors.

5 mm floor covering recess in the hinged cover, if necessary, adjustable to 3, 10 or 12 mm.  
Up to 9 installation devices with 50 mm central plate can be inserted.

Service outlet with locking slider, 3-compartment, for the installation of MT9 mounting support. Three type APMT5 cover plates can be installed.

Floor covering recess in the hinged cover pre-adjusted to 5 mm, if necessary adjustable to 3, 10 or 12 mm.



PA Polyamide

### Master data

|                     |                          |
|---------------------|--------------------------|
| Item number         | 7405466                  |
| Type                | GESR9-2U12T 9011         |
| Description 1       | Service outlet           |
| Description 2       | for universal mounting   |
| Manufacturer        | OBO                      |
| Dimension           | Ø324x68                  |
| Colour              | Graphite black; RAL 9011 |
| Material            | Polyamide                |
| Smallest sales unit | 1                        |
| Unit of quantity    | Piece                    |
| Weight              | 244 kg                   |
| Weight unit         | kg/100 pc.               |

### Technical data

|                                 |                         |
|---------------------------------|-------------------------|
| Number of installable devices   | 12                      |
| Number of mounting boxes        | 3                       |
| Version for                     | Round                   |
| Cable outlet version            | Swivellable cord outlet |
| Floor covering protection frame | yes                     |
| Floor care                      | Dry                     |
| Seal installation option        | no                      |

# Technical data sheet

## GESR9 service outlet with locking slider

Item number: 7405466



### Technical data

|   |                         |
|---|-------------------------|
| Floor height, min.                                | 72 mm                   |
| Suitable for raised floor installation            | yes                     |
| Suitable for screed-flush closed underfloor ducts | yes                     |
| Suitable for screed-covered underfloor ducts      | yes                     |
| Suitable for cavity floor installation            | yes                     |
| Suitable for wet care                             | no                      |
| Suitable for underfloor box                       | 350                     |
| Suitable for underfloor ducts                     | yes                     |
| Device support to accept mounting boxes           | yes                     |
| With floor covering recess                        | yes                     |
| Nominal size for device installation units        | R9                      |
| Frame version                                     | Carpet protection frame |
| Protection rating (IP) when used                  | IP20                    |
| Protection rating (IP) when unused                | IP40                    |
| Protection rating IK code                         | IK08                    |
| Heavy-duty version                                | no                      |
| Installation system type                          | UT4                     |
| Vertical load, large area                         | to 5,000 N              |
| Vertical load, small area                         | to 3,000 N              |
| Approvals   | VDE                     |
| Opening mechanism                                 | Locking slider          |
| Floor covering thickness                          | 5 mm                    |