

Technical data sheet

Ceramic terminal, double

Item number: 7205707



High-temperature-resistant ceramic terminal with four connection options for refitting of the FireBox T series. Tested according to DIN EN 60998-2-1:2004.



Master data

| | |
|---------------------|--------------------|
| Item number | 7205707 |
| Type | TK 16-2 |
| Description 1 | Ceramic terminal |
| Description 2 | for FireBox T |
| Manufacturer | OBO |
| Dimension | 16 mm ² |
| Smallest sales unit | 5 |
| Unit of quantity | Piece |
| Weight | 6.4 kg |
| Weight unit | kg/100 pc. |

Technical data

| | |
|--|------------------|
| Closing plate required | no |
| Connection position | Side |
| No. of terminals | 4 |
| Number of screwless terminals per pole | 4 |
| Version of electrical connection 1 | Screw connection |
| Version of electrical connection 2 | Screw connection |
| Explosion-tested version | no |
| Insulation material | Ceramic |

Technical data sheet

Ceramic terminal, double

Item number: 7205707



Technical data

| | |
|-----------------------------------|--------------------|
| Mounting type | Miscellaneous |
| Nominal cross-section, min. | 16 mm ² |
| Pole number | 1 |
| Permitted temperature range, min. | 250 °C |
| Transparent | no |