
Technical data sheet

Junction box T250, closed, transparent elevated cover

Item number: 2007776





Closed junction box for the connection of cables in indoor and protected outdoor areas. Rectangular design without entries. Suitable for wall and ceiling mounting, on mounting panels and threads in the floor. With the option of fastening inside and to mount via the corner domes. High, transparent cover with quick lock, sealable. Made from halogen-free, UV-resistant materials.

With hat profile rail.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650°C. Impact resistance IK05 according to DIN EN 50102. Clear internal dimensions: 225x173x102 mm



Master data

| Item number | 2007776 |
|---------------------|-------------------------------|
| Туре | T 250 OE HD TR |
| Description 1 | Junction box, closed |
| Description 2 | with high transparent cover |
| Manufacturer | OBO |
| Dimension | 240x190x115 |
| Colour | Light grey; RAL 7035 |
| Material | Polypropylene / polycarbonate |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 50.57 kg |
| Weight unit | kg/100 pc. |
| | |

Technical data sheet

Junction box T250, closed, transparent elevated cover

Item number: 2007776



Technical data

| Expandable | yes |
|-----------------------------------|---|
| Type of insertion | None |
| Type of entry | Cable |
| Type of housing penetration | Without |
| Measured insulation voltage Vi | 500 V |
| Equipment | Without |
| Cover | Transparent |
| Cover fastening | Screwed |
| Entry from rear | yes |
| Entries | None |
| Explosion-tested version | no |
| Flame-resistant | acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C |
| Shape | Rectangular |
| Maintain electrical functions | Without |
| For Ex zone | Without |
| For Ex zone gas | Without |
| For Ex zone dust | Without |
| Fibre-glass reinforced | yes |
| Halogen-free | yes |
| Clear internal dimensions | 225x173x102 mm |
| With screening | no |
| with lid | yes |
| Mounting type | Wall/ceiling mounting |
| Nominal voltage | 500 V |
| Sealable | yes |
| Protection rating | IP66 |
| Protection rating IK code | IK05. |
| Permitted temperature range, max. | 60 °C |
| Permitted temperature range, min. | -5 °C |

BETTERMANN

Technical data sheet

Junction box T250, closed, transparent elevated cover



Item number: 2007776

Technical data

Weatherproof

yes