## **Technical data sheet**U support connector A2

**Item number: 6018408** 





U support connector to connect US 7 supports. Including appropriate fastening material.



A2 Sta

Stainless steel

2B

Bright, treated

### Master data


Item number 6018408 Type VUS 7 A2 Description 1 U support connector Description 2 including truss-head bolts Manufacturer OBO Dimension 190x61 Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1 Unit of quantity Piece		
Description 1 U support connector Description 2 including truss-head bolts Manufacturer OBO Dimension 190x61 Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1 Unit of quantity Piece	Item number	6018408
Description 2 including truss-head bolts  Manufacturer OBO  Dimension 190x61  Material Stainless steel  Surface Bright, treated  Surface standard  Smallest sales unit 1  Unit of quantity Piece	Туре	VUS 7 A2
Manufacturer OBO Dimension 190x61 Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1 Unit of quantity Piece	Description 1	U support connector
Dimension 190x61  Material Stainless steel  Surface Bright, treated  Surface standard  Smallest sales unit 1  Unit of quantity Piece	Description 2	including truss-head bolts
Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1 Unit of quantity Piece	Manufacturer	OBO
Surface Bright, treated Surface standard Smallest sales unit 1 Unit of quantity Piece	Dimension	190x61
Surface standard Smallest sales unit Unit of quantity Piece	Material	Stainless steel
Smallest sales unit 1 Unit of quantity Piece	Surface	Bright, treated
Unit of quantity Piece	Surface standard	
	Smallest sales unit	1
	Unit of quantity	Piece
Weight   110.9 kg	Weight	110.9 kg
Weight unit kg/100 pc.	Weight unit	kg/100 pc.

# **Technical data sheet**U support connector A2





### Dimensions



61

Dimension	61 x 45 x 190
Length	190 mm
Width	61 mm
Height	45 mm

#### Technical data

Type of perforation	3 sides perforated
Version for	Internal connector
Drill hole spacing, centre	50 mm
Suitable for profile shapes	U profile
Hole size	13 x 26 mm
Material thickness	4 mm
With screw accessories	yes
Profile shape	U profile
Rustproof steel, pickled	yes