## **Lightning protection clamp for Kalzip® standing seam profiles**

OBO is bringing guarantees to lightning protection



- The round standing seams are not damaged by incorrectly shaped clamps or tightening torques
- Corrosion-free connection to any Kalzip® roof is possible



- OBO quality developed and tested with international specialists according to testing standard VDE 0185-561-1 (IEC/EN 62561-ED 1, =N)
- Guarantees damage-free and water ingress-free fastening at the round standing seam according to Kalzip® specifications



## Seam clamp for Kalzip® – loose and fixed conductor routing

To comply with Kalzip warranty specifications the use of OBO Kalzip lightning protection clamps is mandatory. Exchanging other clamps in the course of a system check is recommended.





- · For round standing seam systems, fixed conductor routing
- Approved by the manufacturer Kalzip®
- Tested to VDE 0185-561-1 (IEC/EN 62561-1)

| Туре            | Fit<br>mm | Clamping<br>area<br>mm | Lightning current carrying capacity kA |    | Weight kg/100 pcs. | Item No. |
|-----------------|-----------|------------------------|--|----|--------------------|----------|
| RSF 249 8-10 VA | Rd 8-10   | •                      |  | 50 | 14.200             | 5317502  |

V2A Stainless steel, rustproof





- For round standing seam systems, loose conductor routing
- Approved by the manufacturer Kalzip®
- Tested to VDE 0185-561-1 (IEC/EN 62561-1)

|  | Туре             | Fit | Clamping | Lightning current | Pack. | Weight      | Item No. |
|--|------------------|-----|----------|-------------------|-------|-------------|----------|
|  |                  | mm  | area     | carrying capacity | pcs   | kg/100 pcs. |          |
|  |                  |     | mm       | kA                |       |             |          |
|  | RSF 177 20 VA M8 | 8   | 8        | N/50              | 50    | 13.400      | 5317512  |

V2A Stainless steel, rustproof

OBO Bettermann Holding GmbH & Co. KG P.O. Box 1120 58694 Menden GERMANY

Customer Service Tel.: +49 (0)2373 89-1700 Fax: +49 (0)2373 89-1238 export@obo.de

